



For effective isolation of noise and vibration from rotating equipment with speeds of 1000 rpm and above. Typical used to isolate fans, pumps, generators, air-conditioning units and general machinery.

TYPE	DIMENSIONS (mm)							
	H	L	W	D	ØA	ØG	ØK	E
P - 1	28	80	45	60	32	M8	8.5	5
P - 2	32	98	60	76	45	M10	8.5	6
P - 3	44	140	85	104	64	M12	14	6
P - 4	45	165	110	127	100	M12	14	6
PD - 1	35	80	45	60	32	M8	8.5	5
PD - 2	44	98	60	76	45	M10	8.5	6
PD - 3	72	140	85	104	64	M12	14	6
PD - 4	75	165	110	127	100	M12	14	6

TYPE	COLOUR CODE	LOAD (kg)	DEFL. (mm)
P - 1A	BLUE	15	5
P - 1B	WHITE	25	5
P - 1C	GREEN	40	5
P - 1D	YELLOW	60	5
P - 1E	RED	80	5
PD - 1A	BLUE	15	8
PD - 1B	WHITE	25	8
PD - 1C	GREEN	40	8
PD - 1D	YELLOW	60	8
PD - 1E	RED	80	8
P - 2A	BLUE	70	6
P - 2B	WHITE	100	6
P - 2C	GREEN	175	6
P - 2D	YELLOW	250	6
PD - 2A	BLUE	70	10
PD - 2B	WHITE	100	10
PD - 2C	GREEN	175	10
PD - 2D	YELLOW	250	10
P - 3B	WHITE	145	6
P - 3C	GREEN	240	6
P - 3D	YELLOW	340	6
P - 3E	RED	500	6
PD - 3B	WHITE	145	12
PD - 3C	GREEN	240	12
PD - 3D	YELLOW	340	12
PD - 3E	RED	500	12
P - 4B	WHITE	680	6
P - 4C	GREEN	1020	6
P - 4D	YELLOW	1360	6
P - 4E	RED	1800	6
PD - 4B	WHITE	680	12
PD - 4C	GREEN	1020	12
PD - 4D	YELLOW	1360	12
PD - 4E	RED	1800	12

